



NEW !

PORTABLE MONITOR

VECTOR 2

5000 l/min Portable grounds monitor EN15-767 certified With safety valve

- Vector monitor consists of a turret and a base.
- Flow up to 5000 l/min
- **Base**, with **safety shut off** in case of movement, is equipped with large carrying handle, **protected pressure gauge** :
 - Compact when folded
 - 4 stainless steel flexible feet
 - 5 tungsten carbide spikes
 - Swivel inlets: 2x 2.5" BSP F or 4" BSP M
- **Turret** is equipped with **large carrying handle** and **hand wheels** for elevation and rotation adjustment. Thanks to hand wheels no need to lock manually the position: locking is automatic
 - High elevation up to 85° (from 25°)
 - Rotation from 120° left to 80° right
 - Automatic draining valve



Protected pressure
gauge and optional
safety valve



Characteristics

Model	Weight	Dimensions Length x width x height	Item number
Base 2x2.5" BSP F	11.4kg	64 x 24 x 25 cm	CPA-210-OI
Base 2x2.5" NH F			CPA-210-SI
Base 1x4" BSP M	8.7kg	51 x 20 x 22cm	CPA-210-8I
Base 1x4"NH F	9.36kg	53 x 20 x 22cm	CPA-210-9I
Turret 2.5" BSP M	11.3kg	38 x 47 x 31 cm	CPA-310-IP
Turret 2.5" NH M			CPA-310-IS

Folded dimensions

L 65 x l. 65 x H. 52cm



Options

Monitor nozzles: with large and high quality protection jet

- **OneFlow:** fixed flow monitor nozzle
Ref: CDA-023-OI: 2000 l/min @ 6 bar
Ref: CDA-024-OI: 3000 l/min @ 6 bar



- **FlowMatic:** automatic monitor nozzle
Ref: CDA-020-OI: 2000 l/min @ 6 bar
Ref: CDA-021-OI: 3000 l/min @ 6 bar



- **Low expansion foam tube: long reach & very compact (450mm)**
Can be directly screwed on the monitor outlet or installed thanks to Storz coupling for quick connection



Accessories:

- **Siamese 2 x 4" :** to screw on 4" inlet monitor
- **Inlet couplings** on request:
BS336,
Storz,
DSP,
Barcelona...

Reduced cost of ownership:

A very robust monitor and a very light maintenance requirement due to the design and materials used.



ZF.02.314.EN.1